

LIGHT FIBERGLASS EXTENSION LADDER

300 lbs.

TYPE IA LOAD CAPACITY
includes weight of user plus materials

QUICKLATCH® PATENT #5429207

ALUMINUM SWIVEL SAFETY SHOE WITH SHIELD

OUTSIDE SLIDE GUIDES

D-SHAPED RUNGS

MAR-RESISTANT RAIL END CAPS

COMPATIBLE WITH MANY OF OUR EXTENSION LADDER ACCESSORIES

INCLUDING, BUT NOT LIMITED TO...



E03: COMBINATION POLE GRIP AND CABLE HOOK



E04: RIGID POLE GRIP



E34: AUTOMATIC ADJUSTING LADDER LEVELER



LP-2220-01: LEVELOK® QUICK CONNECT SYSTEM (for pre-installed Levelok, use E39)



UP TO...
18% LIGHTER*



1-800-666-2811
www.LOUISVILLELADDER.com

RAIL DEPTH	STACK HEIGHT	INSIDE WIDTH		OUTSIDE WIDTH	
		BASE	FLY	BASE	FLY
3 1/4"	6 1/4"	14 1/4"	13 3/16"	16 1/2"	15 9/16"
MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	APPROX. WEIGHT (LBS)	APPROX. CUBES
L-3025-20	20'	10'	17'	39	7.4'
L-3025-24	24'	12'	21'	45	9'
L-3025-28	28'	14'	25'	51'	10.5'

*than FE7228 when compared with L-3025-28 model (an extension ladder of the same size and duty rating)

L-3025 FLYER 2014 V1 © 2014 LOUISVILLE LADDER, INC. ALL RIGHTS RESERVED

